



Technical details

BET 2.5	
Manufacturer	Exeat d.o.o., Kamnik pod Krimom 62, 1352 Preserje, Slovenia, EU
Type	BET 2.5 closed loop extractor
Capacity (kg)	Up to 0,8
Solvent tank	
Full/useful volume (l)	22,5/18
Dimensions (fi x H mm)	254/620
Max pressure (barG)	18
Extraction column	
Volume (l)	2,5
Dimensions (fi x Hm mm)	76/550
Filtration rate (μm)	5
Number of columns	Max 2
De-wax column (optional)	
Volume (l)	10
Dimensions (fi x Hm mm)	139 x 700
Filtration rate (μm)	5
CRC (optional)	
Volume (l)	2,5
Dimensions (fi x Hm mm)	76/550
Filtration rate (μm)	5
Separator	
Full/useful volume (l)	5/4
Dimensions (fi x H mm)	168/450
Max pressure (barG)	6
Weight (kg)	



Technical details

BET 15	
Manufacturer	Exeat d.o.o., Kamnik pod Krimom 62, 1352 Preserje, Slovenia, EU
Type	BET 15 closed loop extractor
Capacity (kg)	Up to 8
Solvent tank	
Full/useful volume (l)	22,5/18
Dimensions (fi x H mm)	254/620
Max pressure (barG)	18
Extraction column	
Volume (l)	15
Dimensions (fi x Hm mm)	139/1150
Filtration rate (μm)	5
Number of columns	3
De-wax column (optional)	
Volume (l)	20
Dimensions (fi x Hm mm)	139 x 1300
Filtration rate (μm)	5
CRC (optional)	
Volume (l)	2,5
Dimensions (fi x Hm mm)	76/550
Filtration rate (μm)	5
Separator	
Full/useful volume (l)	18/15
Dimensions (fi x H mm)	254/500
Max pressure (barG)	6
Weight (kg)	



Technical details

BET 30	
Manufacturer	Exeat d.o.o., Kamnik pod Krimom 62, 1352 Preserje, Slovenia, EU
Type	BET 30 closed loop extractor
Capacity (kg)	Up to 8
Solvent tank	
Full/useful volume (l)	22,5/18
Dimensions (fi x H mm)	254/620
Max pressure (barG)	18
Extraction column	
Volume (l)	15
Dimensions (fi x Hm mm)	139/1150
Filtration rate (μm)	5
Number of columns	3
De-wax column (optional)	
Volume (l)	20
Dimensions (fi x Hm mm)	139 x 1300
Filtration rate (μm)	5
CRC (optional)	
Volume (l)	2,5
Dimensions (fi x Hm mm)	76/550
Filtration rate (μm)	5
Separator	
Full/useful volume (l)	18/15
Dimensions (fi x H mm)	254/500
Max pressure (barG)	6
Weight (kg)	